Data Sheet WALLTEX SB 160g

	1
USE	(Permenant type) Self adhesive fabric Media for inkjet printers for Solvent, UV, Latex
	for indoor/outdoor, (Indoor is Recommanded for white color Image)
	Self adhesive coated on the back side, Matt Surface
	Sticker, Phoster, Interior, Wall Paper(point wall paper), Window Graphics, Decoration, Photo Album & Self adhesive Application (Easy Corner Covering)
COMPOSITION	Front side: Printing Textile (100% Polyester woven fabric cloth)
	coated by silica and some additives in Acrylic binders & Poly Urathane
	Middle : Solvent based Acrylic Adhesive
	Back: Paper Liner (90g/m², White colored, Neutral)
FABRIC DENSITY	150d x 150d
COATED THICKNESS	200,4m ± 30%
COATED WEIGHT	134g/m² ± 30%
Total Thickness	350,µm ± 30% (with liner)
Total Weight	305g/m² ± 30% (with liner)
Thickness of Liner	150µm± 20%
Weight of Liner	140g± 20%
Weight (fabric+glue)	165g/m² ± 30%
Core	3 inch
HEALTH AND SAFETY	This product will not cause any special health or safety hazard, when used as intended. Sharp edges of product may cut operator's skin
FIRE HAZARD	Burning rates and hazards of this product are similar to other polyester-based products of equivalent thickness. Avoid sources of fires .
HANDLING	Put the product around 1 hour in room temperature (over 15°c) before using
	if you clean and dry the surface before attaching, its result will be better
	On the smooth surface like glass or refrigerator, it works as removable
	and it can be attach variety range of surface without primer.
	up to raw material, surface treatment and roughness of surface , Temperatuere etc adhesnion can be different Please test our material befor using.
	if glue remains on the surface like smooth and flat surface like glass , you can wash it with water
STORAGE	Keep it in from 30 to 65% relative humidity and 10 ~ 30℃. Storage it in the original package(cardboard box and PE bag). Avoid sources of fires
WASTE DISPOSAL	May be disposed of as domestic waste. Disposal in accordance with local, state or federal regulations.