

Whiteboard PP Dryapply ASLAN WBL 998



Glossy, PVC free whiteboard film for easy dry applications even in large formats

The glossy self-adhesive film turns smooth surfaces into writable whiteboards. The scratch resistant coating ensures that writings with whiteboard markers can be wiped off dry without leaving any shadows or ghostings. Finest air release channels allow air bubbles to be wiped out with ease and make the application of the PVC free self-adhesive film fast and easy.

For any further information please contact our technical advisory service:
+49 2204 70880

Construction

Face film:	PP with special lacquering	
Thickness:	~ 150 µm	
Adhesive:	Polyacrylate adhesive	Square quantity: ~ 25 g/m²
Release liner:	Embossed silicone paper, PE coated on both sides	Square weight: ~ 130 g/m²

Characteristics

Adhesive strength (ASTMD-903):	immediately: after 72 hours:	~ 6 N/25 mm ~ 12 N/25 mm
Dimensional stability:	applied onto aluminium after 48 hours stored at 70 °C (25 x 25 cm)	no shrinkage measurable
Chemical resistance:	In a preece test of 24 hours the applied film is resistant to most petroleum-based oils, greases and aliphatic solvents, mild acids, alkalis and salts.	
Temperature:	Application temperature: Service temperature range:	min. 15 °C -30 °C up to +80 °C
Durability:	Up to 2 years outdoors, with vertical exposure, in central-European climate.	

ASLAN, Schwarz GmbH & Co. KG
Oberauel 2 · 51491 Overath · Germany
fon +49 2204 70880 · fax +49 2204 70850
e-mail info@ASLAN-Schwarz.com



www.ASLAN-Schwarz.com

ASLAN®
EXPERTISE IN SELF-ADHESIVE FILMS

Whiteboard PP Dryapply ASLAN WBL 998



Processing

Application:

The film is to be applied dry only. The surface must be free of dust, grease and oil.

Important:

We do not recommend a large-scaled application of whiteboard films with mounting tapes. The writable surface of the film can be damaged by taking off the tape so removability cannot be guaranteed anymore. If it is nevertheless necessary using a mounting tape we recommend a tape with low adhesion. The tape should be taken off from the middle of the material to the edge.

Cleaning:

Writings with whiteboard markers can be easily wiped off dryly using a microfibre cloth, without leaving any ghosting and shadows. If you used by mistake inappropriate pens, i.e. a permanent marker, you can clean the films with alcohol or white gas for cleaning purposes without leaving any residues.

Storage:

Before application the film can be stored for minimum 2 years from date of production. The film must be stored at room temperature (15-25 °C) and a relative humidity of the air of 50-60%. To avoid pressure points appearing on the roll surface, we recommend the rolls be stored either vertical standing or for this purpose designed 'hanging' racks.

State 7|2019

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.

ASLAN, Schwarz GmbH & Co. KG
Oberauel 2 · 51491 Overath · Germany
fon +49 2204 70880 · **fax** +49 2204 70850
e-mail info@ASLAN-Schwarz.com



www.ASLAN-Schwarz.com

ASLAN®
EXPERTISE IN SELF-ADHESIVE FILMS