

What makes DFT B-FLEX film so unique and special?



the films features remain unchanged so you can count on the same premium quality over time.



APPLICATION FROM 130°C / 265°F

to be able to customize many different fabrics and delicate materials.



HOT PEEL



excellent color rendering for intensity and depth.



SOFT TOUCH EFFECT

smooth and soft results on the application due to a special chemical formula of the film.



(U) MAXIMUM **PERFORMANCE ON SMALL DETAILS**

perfect peel avoiding dragging details.



(=♥) PROMPT DELIVERY

production and warehouse based in Italy simplify order management, it's possible to order small quantities and receive them quickly. You don't have to fill the containers!









TECHNICAL FEATURES

Hot peel (or cold peel) with application range from 130°C/265°F to 160°C/ 320°F*.

Application time starting at 4 seconds*.

Optimal powder glue melting range from 85°C/185°F to 140°C/ 250°F* (internal oven temperature).

Matt finish.

No residues of powder glue or ink left on the film.

For brighter colors and durability, a **second** press may be needed due to temperature and application time.

INSTRUCTIONS

PRINTING SET UP

Set up a white ink which allows for correct layering of inks. White ink can also be used as a full-on color.

- **PRINT ON TRANSFER FILM** Mirror design.
- **GLUE APPLICATION** Manually or with automatic shaker.
- **OVEN CURING** Internal oven temperature between 85°C/185°F and 140°C/250°F*.
- **HEAT PRESSING TRANSFER ON GARMENT**


Follow the suggested technical features.

LINER REMOVAL Hot and semi-hot, depending on temperature and application time used.

STANDARD SIZES AVAILABLE


ROLLS

- h 30 cm x 100 mt / 11,8" x 109 yd
- h 60 cm x 100 mt / 23,6" x 109 yd



SHEETS

- A3 11,7" x 16,5"
- cm 40x50





CUSTOM SIZES available on demand.



Problems during the printing stage?

The DTF world is new and has a lot of variables to consider. You may have issues at first without really understanding why.

Don't give up, call us for help!

Our experience is at your disposal. We will work through the problem together, so you'll understand how to solve the issue and get the perfect application!

HEADQUARTERS

B-FLEX ITALIA S.r.I.

Via 1º Maggio, 44 | 36050 Sovizzo (VI) | ITALY Tel +39 0444.028139 | info@b-flexitalia.com

www.b-flexitalia.com

NORTH AMERICA BRANCH

B-FLEX AMERICA LLC

468 Columbia Industrial Blvd | Evans | GA 30809 Tel +1 (866) 440-BFLX | info@b-flexamerica.com

www.b-flexamerica.com

ASIA-PACIFIC BRANCH

B-FLEX PACIFIC PTY LTD

5 Raceway Pl | Eastern Creek | NSW 2766 Sydney | Australia Tel +61 2 8662 0801 | info@b-flexpacific.com

www.b-flexpacific.com

fst The technical info depending from the setting of DTF printer, glue and ink used.