

# ReTac<sup>®</sup>

## Smooth 150

**EASY APPLICATION AND REMOVAL**

Our 6 mil (150 $\mu$ ), white polymeric printable PVC film with ReTac<sup>®</sup> ultra removable adhesive technology is designed for graphics that need to be easily installed, removed and re-positioned.

Dimensionally stable, ReTac<sup>®</sup> Smooth 150 can be applied and re-positioned multiple times without stretching or tearing. And, with ReTac<sup>®</sup> on the back, you never have to worry about adhesive setting up, being left behind, or damaging the surface it is adhered to when graphics are removed.

ReTac<sup>®</sup> Smooth 150 has a Class 0 Fire Rating for surface spread of flame.

- IDEAL FOR INTERIOR WALL GRAPHIC APPLICATIONS
- PERFECT FOR APPLICATION IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

**Product Code: RTF and RTG**

**150** White  
micron Phthalate-Free  
Polymeric PVC Matte or Gloss



(Eco)Solvent  
Latex  
UV



ReTac<sup>®</sup> ultra removable  
and re-positionable  
adhesive



Widths up to 1370mm



**5 YEARS DURABILITY**  
INTERIOR AND EXTERIOR  
(2 YEAR REMOVABILITY EXTERIOR)



### APPLICATIONS

- Smooth Flat Surfaces
- Point Of Sale Graphics
- Interior Décor
- Decals & Stickers

Certified for  
HP Latex Inks

**DRYTAC<sup>®</sup>**  
ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

# ReTac®

## Smooth 150

ReTac® Smooth 150 is a 6 mil (150µ) printable white, phthalate-free polymeric PVC film, coated on one side with ReTac® ultra removable adhesive. The adhesive is protected by a single-sided, siliconised clay coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy application and removal of vibrant graphics to a wide range of substrates. ReTac® Smooth 150 can be easily applied, re-positioned and removed without surface damage or loss of adhesion.

- RETAC® IS A PHTHALATE-FREE FILM.
- IDEAL FOR REMOVABLE WALL DECALS, APPLIQUES AND WALL MURALS.
- SUITABLE FOR USE ON MOST INDOOR SURFACES, PAINTED WALLS, MELAMINE, GLASS, AND LOW SURFACE ENERGY SUBSTRATES.
- RETAC® SMOOTH 150 HAS A CLASS 0 FIRE RATING ACCORDING TO UK STANDARDS FOR SURFACE SPREAD OF FLAME, MAKING IT PERFECT FOR APPLICATIONS IN PUBLIC AREAS THAT REQUIRE COMPLIANCE WITH STRICT FIRE REGULATIONS, SUCH AS AIRPORTS, HOTELS AND HOSPITALS.

Please Note: Plasticizer migration from some PVC substrates could cause adhesive residue being left behind upon removal

**For more information, performance and warranty guide lines please contact your local Drytac office.**

© 2018 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Matte or Gloss White Polymeric PVC
<b>Adhesive</b>	ReTac® ultra removable and re-positionable adhesive technology
<b>Release Liner</b>	135 gsm 1 side siliconised clay coated Kraft paper

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	6 mil (150µ)	6.9 mil (172µ)
<b>Adhesive Layer</b>	0.9 mil (22µ)	
<b>Film/Adhesive Ratio</b>	6:0.9	
<b>UV Protection Factor</b>	Not Applicable	
<b>Outdoor Durability</b>	5 year; 2 years removability	
<b>Application Temperature</b>	>41°F (5°C)	
<b>Service Temperature Range</b>	-4°F to 149°F (-20°C to 65°C)	
<b>Flame Retardancy</b>	Class 0 BS 476 - Part 6 & 7 Fire Rating	
<b>Shelf Life</b>	2 years	
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity	

### OVERLAMINATE RECOMMENDATIONS

When using ReTac® Smooth 150, an overlaminate can be used for maximum life expectancy. Products recommended for use with ReTac® Smooth 150 are Drytac's Weathershield™ overlaminates.

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

105 Nuggett Court,  
Brampton,  
Ontario, L6T 5A9,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5601 Eastport Boulevard,  
Richmond,  
Virginia, 23231,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013

# DRYTAC®

## ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)