













## MEDIATEX® Covertex FR

	Einheit Unit	Norm Standard	Wert Value
Substrat Substrate		DIN 60001	100% Polyester 100% polyester
Bindung Weave		DIN ISO 9354	Gewebe woven fabric
Flächengewicht Weight	 g/m <sup>2</sup>	DIN EN ISO 2286-2	240
Brandverhalten Fire retardancy		DIN 4102 B1 (in Bearbeitung / in process)	ja yes
Tintenart Type of ink		  	alle Solventtinten, UV-härt.*, Latextinten all kinds of solvent, UV-curable*, latex inks
Anwendung Application			innen indoor
Breite Width	 cm inch	DIN EN ISO 2286-1	max. 310 max. 122
Druckseite Print side			Breite < 3m: Druckseite außen Breite > 3m: Druckseite innen width < 3m: print side outside width > 3m: print side inside
Rollenlänge Roll length	 m		30 - 50 ± 0,5

### Anwendungen Applications



Roll up / roll up  
Wandverkleidung / wall covering  
Dimout / dimout  
Frontlit / frontlit  
Display / display  
Rahmensysteme / framing systems  
Banner / banner

### Besonderheiten Characteristics

- höchste Druckqualität  
highest print quality
- kein Weißbruch  
no white cracking / crazing
- kalt schneidbar  
trimming cold
- leichte Montage  
easy to mount
- schnelle Falterholung  
fast crease recovery
- bei Wandverkleidung: Wand einkleistern  
for wall covering: "paste the wall"

\* Da UV-härtende Tinten noch nachhärten, ist mit einem Schüsseln zu rechnen.

Please consider the risk of „curling“ because UV-curable inks will still be hardening after a while.

All details are nominal values and are subject to change within usual tolerances (± 5%). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 10/2017